



## **5MM AND 10MM PROJEX SHOCKMAT**

SHOCKMAT has many commercial and industrial applications and is ideal as a protective matting medium. It is also widely used for waterproofing membranes protection, walkways and to protect the ballast on railway bridges. As a membrane protective medium SHOCKMAT is cheaper and easier to install than tiles or concrete screeds - you simply just roll it out.

A roll of SHOCKMAT is an easy to handle roll of reclaimed rubber, sourced from the tyre industry, bonded together with high quality polyurethanes.

### ***PROJEX SHOCKMAT HAS OUTSTANDING IMPACT SOUND DEADENING PROPERTIES IN MANY RESIDENTIAL AND COMMERCIAL APPLICATIONS INCLUDING:***

- Office Buildings
- Apartments, duplexes, units
- Houses
- Hotels
- Hospitals
- Schools, libraries, universities
- Areas where sound transmission may be a problem.

### ***PROJEX SHOCKMAT'S FEATURES ARE:***

- Meets and exceeds Australian acoustic building requirements
- Can be loose laid or bonded applications
- Can be laid under tiles, stone or timber floors
- Can be used over a wide service temperature range
- Environmentally friendly (made from recycled rubber)
- Manufactured under a quality system certified as complying with ISO 9001 by an accredited certification body.



PROJEX GROUP PTY LTD

ACN 003 859 916

PO Box 98 Matraville NSW 2036

PH: (02) 8336 1666 FX: (02) 9661 9925

e-mail: [mail@projex.com.au](mailto:mail@projex.com.au) website: [www.projex.com.au](http://www.projex.com.au)



### **SPECIFICATIONS:**

- Complies to Australian Standards (ASTM E 989-89) CSIRO tested 2007
- (in accordance with ISO 140-8:1997 & ISO 140-6 and AS 1276)
- Spread of flame index: AS 1530.3
- Material thickness: 5mm (1.25m x 12m)
- Material thickness: 10mm (1.25m x 6m)
- Material density: 425 kg/cubic meter
- Supplied in roll form therefore no curing required after installation
- Temperature stability: -30 + 80 degrees C
- Classification as building material: B2
- Exceeds BCA requirements

### **IN ADDITION IT CAN BE USED AS A MEMBRANE PROTECTION OR NON-SLIP WALKWAY OVER:**

- Bitumen
- Acrylic membranes
- Polyurethanes
- PVC sheet
- Polyester-PVC sheet
- Polyurea membranes
- Butyl-rubber membranes
- Concrete
- Timber
- Steel

## **TECHNICAL ASSISTANCE**

Projex staff are available on request to provide any assistance required.  
Call us on (02) 8336 1666. Email us at [mail@projex.com.au](mailto:mail@projex.com.au)  
Or visit our website at [www.projex.com.au/shockmat](http://www.projex.com.au/shockmat)