



SAFETY DATA SHEET

BOSTIK N40 PRIMER
Revision Number 2.03

Revision date 07-Nov-2022
Supersedes Date: 22-Sep-2019

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name BOSTIK N40 PRIMER

Product Code(s)
30608476
30608476; 30608603

Other means of identification

Proper Shipping Name Isopropanol

UN number or ID number UN1219

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Primers

Uses advised against No information available

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Flammable liquids	Category 2 - (H225)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitization	Category 1 - (H317)
Specific target organ toxicity (single exposure)	Category 3 - (H336)

Label elements

Flame
Exclamation mark
Corrosion

SAFETY DATA SHEET

BOSTIK N40 PRIMER
Revision Number 2.03

Revision date 07-Nov-2022
Supersedes Date: 22-Sep-2019



Signal word
DANGER

Hazard statements

H225 - Highly flammable liquid and vapor
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H336 - May cause drowsiness or dizziness

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace
Wear protective gloves/clothing and eye/face protection
Use only outdoors or in a well-ventilated area
Ground and bond container and receiving equipment
Use non-sparking tools
Take action to prevent static discharges
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container closed
Keep cool
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a doctor
IF ON SKIN: Wash with plenty of water and soap
If skin irritation or rash occurs: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a doctor if you feel unwell
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Precautionary Statements - Storage

Store in well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

In use, may form flammable/explosive vapor-air mixture.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
Isopropyl alcohol	67-63-0	>60

SAFETY DATA SHEET

BOSTIK N40 PRIMER
Revision Number 2.03

Revision date 07-Nov-2022
Supersedes Date: 22-Sep-2019

N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	0 - <10
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Get immediate medical attention. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable extinguishing media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous combustion products Carbon oxides. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Silicon oxides.

Special protective actions for fire-fighters

SAFETY DATA SHEET

BOSTIK N40 PRIMER
Revision Number 2.03

Revision date 07-Nov-2022
Supersedes Date: 22-Sep-2019

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code •2YE

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

SAFETY DATA SHEET

BOSTIK N40 PRIMER
Revision Number 2.03

Revision date 07-Nov-2022
Supersedes Date: 22-Sep-2019

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Protect from moisture.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical name	Australia
Isopropyl alcohol 67-63-0	TWA: 400 ppm TWA: 983 mg/m ³ STEL: 500 ppm STEL: 1230 mg/m ³

OEL as published by Safe Work Australia

Biological occupational exposure limits

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Hand protection Wear suitable gloves. Impervious gloves.

Respiratory protection Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapors filter conforming to EN 14387.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid
Color Colorless
Odor Solvent
Odor threshold No information available

Property	Values	Remarks • Method
pH	No data available	
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	

SAFETY DATA SHEET

BOSTIK N40 PRIMER
Revision Number 2.03

Revision date 07-Nov-2022
Supersedes Date: 22-Sep-2019

Initial boiling point and boiling range	82 °C
Flash point	12 °C
Evaporation rate	No data available
Flammability	Not applicable for liquids .
Flammability Limit in Air	
Upper flammability or explosive limits	12
Lower flammability or explosive limits	1.8
Vapor pressure	4.4
Relative vapor density	No data available
Relative density	No data available
Water solubility	No data available
Solubility(ies)	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	No data available
Explosive properties	No information available
Oxidizing properties	No information available
<u>Other information</u>	
Solid content (%)	No information available
Liquid Density	0.8 g/cm ³
VOC content	No information available

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Protect from moisture.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Carbon oxides.

Section 11: Toxicological information

SAFETY DATA SHEET

BOSTIK N40 PRIMER
Revision Number 2.03

Revision date 07-Nov-2022
Supersedes Date: 22-Sep-2019

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	40,000.00 mg/kg
ATEmix (inhalation-vapor)	1,200.00
ATEmix (inhalation-dust/mist)	27.50 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Isopropyl alcohol	>5000 mg/Kg	= 4059 mg/kg (Oryctolagus cuniculus)	=72600 mg/m ³ (Rattus) 4 h
N-(3-(trimethoxysilyl)propyl)ethylenediamine	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44 mg/L air

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

Component Information					
Isopropyl alcohol (67-63-0)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			Irritant

Respiratory or skin sensitization May cause an allergic skin reaction.

Component Information

SAFETY DATA SHEET

BOSTIK N40 PRIMER
Revision Number 2.03

Revision date 07-Nov-2022
Supersedes Date: 22-Sep-2019

Isopropyl alcohol (67-63-0)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization	Guinea pig		No sensitization responses were observed

Germ cell mutagenicity No information available.

Component Information			
Isopropyl alcohol (67-63-0)			
Method	Species	Exposure route	Results
OECD Test No. 476: In vitro Mammalian Cell Gene Mutation Test	Hamster, in vitro		Not mutagenic

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
Isopropyl alcohol 67-63-0			Group 3

Legend

IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity No information available.

STOT - single exposure May cause drowsiness or dizziness. May cause respiratory irritation.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Isopropyl alcohol 67-63-0	EC50 72 h > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h > 1400000 ?g/L (Lepomis macrochirus)	-	EC50: =13299mg/L (48h, Daphnia magna)
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static

Persistence and degradability

Persistence and degradability No information available.

SAFETY DATA SHEET

BOSTIK N40 PRIMER
Revision Number 2.03

Revision date 07-Nov-2022
Supersedes Date: 22-Sep-2019

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Isopropyl alcohol 67-63-0	0.05
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-0.3

Mobility

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Section 14: Transport information

ADG

UN number or ID number UN1219
UN proper shipping name Isopropanol
Transport hazard class(es) 3
Packing group II
Limited quantity (LQ) 1 L
Description UN1219, Isopropanol, 3, II

Hazchem code •2YE

IATA

UN number or ID number UN1219
Transport hazard class(es) 3
Packing group II
ERG Code 3L
Special Provisions A180
Limited quantity (LQ) 1 L
Description UN1219, Isopropanol, 3, II

IMDG

UN number or ID number UN1219
Transport hazard class(es) 3
Packing group II
EmS-No F-E, S-D
Limited Quantity (LQ) 1 L
Marine pollutant NP
Description UN1219, Isopropanol, 3, II, (12°C c.c.)

SAFETY DATA SHEET

BOSTIK N40 PRIMER
Revision Number 2.03

Revision date 07-Nov-2022
Supersedes Date: 22-Sep-2019

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III
Liquids with flash points <61°C kept above their boiling points
at ambient conditions

Threshold quantity (T)

50 000

200

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Isopropyl alcohol 67-63-0	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

AIIIC Listed
NZIoC Listed
ENCS Listed
IECSC Listed
KECL Listed
PICCS Listed

Legend:

AIIIC - Australian Inventory of Industrial Chemicals
NZIoC - New Zealand Inventory of Chemicals
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

SAFETY DATA SHEET

BOSTIK N40 PRIMER
Revision Number 2.03

Revision date 07-Nov-2022
Supersedes Date: 22-Sep-2019

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 07-Nov-2022

Revision Note

SDS sections updated; 3, 14.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet